

SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/8

Beauty-Cast

Revision 0
Revision date 2025-01-09

1.1. Product identifier

Product name Beauty-Cast

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Foundry material.

1.3. Details of the supplier of the safety data sheet

Company Ransom & Randolph

Address 3535 Briarfield Boulevard Maumee, Ohio 43537 USA

Web www.ransom-randolph.com

Telephone +1 (419) 865-9497 **Fax** +1 (419) 865-9997

Email SDS@ransom-randolph.com

Email address of the competent person

SDS@ransom-randolph.com

1.4. Emergency telephone number

Emergency telephone number

Company

USA +1 419 865 9497

Ransom & Randolph Co.

08:00-17:00 (US Eastern Std. / GMT minus 5)

For medical advice contact: NHS 111 in England: 111 NHS 24 in Scotland: 111

NHS Direct in Wales: 111 or 0845 4647

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008

Carc. 1A: H350; STOT RE 1: H372;

2.2. Label elements

This substance / mixture has been classified in accordance with the US Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are presented, and minor ingredient composition maybe withheld, to protect trade secrets.

Hazard pictograms



Revision 0 Revision date 2025-01-09

2.2. Label elements

Signal Word	Danger
Hazard Statement	Carc. 1A: H350 - May cause cancer inhalation.
	STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure
	inhalation.
Precautionary Statement:	P201 - Obtain special instructions before use.
Prevention	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
	P264 - Wash (hands) thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P285 - In case of inadequate ventilation wear respiratory protection.
Precautionary Statement:	P308+P313 - IF exposed or concerned: Get medical advice/attention.
Response	P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement:	P405 - Store locked up.
Storage	
Precautionary Statement:	P501 - Dispose of contents/container to local and national regulations
Disposal	
2.3. Other hazards	
Other hazards	Product contains respirable crystalline silica (RCS).
Further information	

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc.	Classification
				Number	(%w/w)	
quartz > 10 %		14808-60-7	238-878-4		60 - 70%	Carc. 1A: H350; STOT RE 1: H372:
calcium sulfate. (Plaster of Paris)		26499-65-0			30 - 40%	,
Barium chloride	056-004-00-8	10361-37-2	233-788-1		0.5 - 1%	Acute Tox. 3: H301; Acute Tox. 4: H332;

Not applicable. PBT and vPvB assessment.

Particle Characteristics

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.					
Eye contact	May cause irritation to eyes.					
Skin contact	May cause irritation to skin.					

Revision 0 Revision date 2025-01-09

	Revision date 2025-01-09
4.2. Most important symptoms a	and effects, both acute and delayed
Ingestion	May cause irritation to mucous membranes.
4.3. Indication of any immediate	medical attention and special treatment needed
Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.
SECTION 5: Firefighting me	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear suitable protective clothing.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Avoid raising dust.
6.2. Environmental precautions	
	Use appropriate container to avoid environmental contamination.
6.3. Methods and material for co	ontainment and cleaning up
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	
	See section for further information.
SECTION 7: Handling and s	torage
7.1. Precautions for safe handlir	ng
	Avoid formation of dust. Ensure adequate ventilation of the working area. <. OEL: Occupational exposure limit. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep containers tightly closed.
7.3. Specific end use(s)	
	Foundry material.
SECTION 8: Exposure contr	ols/personal protection
8.1. Control parameters	
	all respirable crystalline silica - sum of all types - quartz + cristobalite TWA PEL OSHA (respirable fraction) 0.050 mg/m3

Revision 0
Revision date 2025-01-09


8.1. Control parameter	S
------------------------	---

Action Level OSHA (respirable fraction) 0.025 mg/m3.

8.1.1. Exposure Limit Values

calcium sulfate. (Plaster of Paris)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10 inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Revision 0 Revision date 2025-01-09

9.1. Information on basic physical and chemical properties

Appearance	Powder
• •	
Odour threshold	
	Not applicable.
	Not applicable.
	Not applicable.
Initial boiling point	
	Not applicable.
Evaporation rate	
Flammability (solid, gas)	
Vapour Flammability	··
Upper Explosive Limit	
Lower Explosive Limit	••
Vapour pressure	
	••
Density / Relative Density	Not applicable.
Water solubility	Not applicable.
Fat Solubility	Not applicable.
Partition coefficient	Not applicable.
(n-octanol/water)	
Partition coefficient	Not applicable.
Autoignition temperature	Not applicable.
Decomposition temperature	1450 °C
Viscosity	Not applicable.
Explosive properties	Not applicable.
Oxidising properties	Not applicable.

9.2. Other information

Conductivity	Not applicable.
Surface tension	Not applicable.
Specific gravity	Not applicable.
Gas group	Not applicable.

SECTION 10: Stability and reactivity

		Rea	

Not applicable.			

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No Significant Hazard.

10.4. Conditions to avoid

Moisture.

10.5. Incompatible materials

No Significant Hazard.

Revision 0 Revision date 2025-01-09

10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information

11.1 Information on hazard classes

Acute toxicity

Skin corrosion/irritation

Serious eye damage/irritation

Respiratory or skin sensitisation

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT-single exposure

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged or repeated exposure may cause irritation to skin and mucous membranes.

No irritation expected.

No sensitizaton effects reported.

No mutagenic effects reported.

Known Human Carcinogens (Category 1).

No observed effect level. No observed effect concentration.

No known adverse health effects.

Chronic effects

Prolonged inhalation of respirable crystalline silica

In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:

"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."

(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)

There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).

Aspiration hazard

Repeated or prolonged exposure

No Significant Hazard.

Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

11.1.4. Toxicological Information

Beauty-Cast Oral Mouse LD50: 5000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Beauty-Cast Fish LC50/96h: 10000.0000 mg/l

12.2. Persistence and degradability

No data is available on this product.

Revision 0

Revision date 2025-01-09

	Revision date 2025-01-09
12.3. Bioaccumulative potential	
	Does not bioaccumulate.
Partition coefficient	
	Beauty-Cast Not applicable.
12.4. Mobility in soil	
12.4. Wobility III Soil	Not determined.
12.5. Results of PBT and vPvB	1
12.5. Results of FBT and VI VB	Not determined.
12.7 Other adverse effects	Not determined.
12.7 Other adverse effects	Not applicable.
SECTION 13: Disposal cons	
13.1. Waste treatment methods	
	Dispose of in compliance with all. local and national regulations.
Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	
	Empty containers can be sent for disposal or recycling.
SECTION 14: Transport info	rmation
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es	;)
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	
	The product is not classified as dangerous for carriage.
14.6. Special precautions for user	
	The product is not classified as dangerous for carriage.
14.7 Maritime Transport in bulk according to IMO instruments	
	The product is not classified as dangerous for carriage.
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	

Revision 0 Revision date 2025-01-09

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

U.S. FEDERAL REGULATIONS: SC20 family of investments. CERCLA 103 Reportable Quantity: is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Chronic health quartz.

Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

INTERNATIONAL REGULATIONS:

Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).

Canadian WHMIS Classification: Class D2A (Chronic toxic effects), D2A (Carcinogenicity).

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Text of Hazard Statements in Section 3

Carc. 1A: H350 - May cause cancer .

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 4: H332 - Harmful if inhaled.

Further information

Training

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.