

# SAFETY DATA SHEET

according to Regulation (EU) 2020/878

Page 1/8

## Cristobalite™

Revision 0

Revision date 2025-01-09

SECTION 1: Identification of the substance/mixture and of the company/undertaking				
1.1. Product identifier				
Product name	Cristobalite™			
1.2. Relevant identified uses of t	he substance or mixture and uses advised against			
Description	Foundry material.			
1.3. Details of the supplier of the	e safety data sheet			
Company	Ransom & Randolph			
Address	3535 Briarfield Boulevard			
	Maumee, Ohio 43537 USA			
Web	www.ransom-randolph.com			
Telephone	+1 (419) 865-9497			
Fax	+1 (419) 865-9997			
Email	SDS@ransom-randolph.com			
Email address of the	rcarter@ransom-randolph.com			
competent person				
1.4. Emergency telephone number				
Emergency telephone number	USA +1 419 865 9497			
Company	Ransom & Randolph Co.			
	08:00-17:00 (US Eastern Std. / GMT minus 5)			
	For medical advice contact:			
	NHS 111 in England: 111			
	NHS 24 in Scotland: 111			
	NHS Direct in Wales: 111 or 0845 4647			
SECTION 2: Hazards identifi	cation			
2.1. Classification of the substar	ice or mixture			
2.1.2. Classification - EC	Carc. 1A: H350; STOT RE 1: H372;			
1272/2008				
2.2. Label elements				
	This substance / mixture has been classified in accordance with the US Federal OSHA Hazard			
	Communication Standard 29CFR 1910.1200. Substance concentration band-ranges are			
	presented, and minor ingredient composition maybe withheld, to protect trade secrets.			
Hazard pictograms				
Copyright © 2025 ChemSoft. All rights reserved	Print date 2025-01-09			
	ChemSoft EH&S			

2.2. Label elements		
Signal Word	Danger	
Hazard Statement	Carc. 1A: H350 - May cause cancer inhalation. STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure inhalation.	
Precautionary Statement: Prevention	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P260 - Do not breathe dust/fume/gas/mist/vapours/spray.</li> <li>P264 - Wash (hands) thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</li> </ul>	
	P285 - In case of inadequate ventilation wear respiratory protection.	
Precautionary Statement: Response	P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell.	
Precautionary Statement: Storage	P405 - Store locked up.	
Precautionary Statement: Disposal	P501 - Dispose of contents/container to local and national regulations	
2.3. Other hazards		
Other hazards	Product contains respirable crystalline silica (RCS).	
Further information		
	Not applicable. PBT and vPvB assessment.	

### SECTION 3: Composition/information on ingredients

3.2. Mixtures

### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
silica - cristobalite		14464-46-1	238-455-4		30 - 40%	o Carc. 1A: H350; STOT RE 1: H372;
calcium sulfate. (Plaster of Paris)		26499-65-0			30 - 40%	
quartz > 10 %		14808-60-7	238-878-4		20 - 30%	o Carc. 1A: H350; STOT RE 1: H372;

### **Particle Characteristics**

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.	
Skin contact	Wash with soap and water.	
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.	
4.2. Most important symptoms and effects, both acute and delayed		
Inhalation	May cause irritation to respiratory system.	
Eye contact	May cause irritation to eyes.	
Skin contact	May cause irritation to skin.	



Revision	0
	•

Revision date 2025-01-09

4.2. Most important symptoms a	nd effects, both acute and delayed
Ingestion	May cause irritation to mucous membranes.
4.3. Indication of any immediate	medical attention and special treatment needed
Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear suitable protective clothing.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Avoid raising dust.
6.2. Environmental precautions	
	Use appropriate container to avoid environmental contamination.
6.3. Methods and material for co	ntainment and cleaning up
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	
	See section for further information.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handlin	g
	Avoid formation of dust. Ensure adequate ventilation of the working area. <. OEL: Occupational exposure limit. In case of insufficient ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep containers tightly closed.
7.3. Specific end use(s)	
	Foundry material.
SECTION 8: Exposure control	ols/personal protection
8.1. Control parameters	
	all respirable crystalline silica - sum of all types - quartz + cristobalite TWA PEL OSHA (respirable fraction) 0.050 mg/m3



## Revision 0

Revision date 2025-01-09

### 8.1. Control parameters

	Action Level OSHA (respirable fraction) 0.0	25 mg/m3.		
8.1.1. Exposure Limit Values				
calcium sulfate. (Plaster of Paris)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -		
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -		
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -		
	inhalable dust:	inhalable dust:		
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -		
	respirable dust:	respirable dust:		

### 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area. <. OEL: Occupational exposure limit.	
8.2.2. Individual protection measures	Wear:. Protective clothing. applicable international Standards are. EN13982, ANSI 103 or =.	
Eye / face protection	Avoid contact with eyes. Wear:. Approved safety goggles. safety glasses with side-shields. applicable international Standards are. EN166, ANSI Z87.1 or =.	
Skin protection - Handprotection	Avoid contact with skin. Wear suitable gloves. applicable international Standards are. EN374, ASTM F1001 or =.	
Respiratory protection	Exposure above the recommended occupational exposure limit (OEL) may cause adverse health effects.	
	After selection by a Qualified person. Wear:. Suitable respiratory equipment. applicable internationa Standards are. EN140, EN143, ASTM F2704-10 or =.	
8.2.3. Environmental exposure controls	Use appropriate container to avoid environmental contamination.	
SECTION 9: Physical and chemical properties		

9.1. Information on basic physical and chemical properties



 Revision
 0

 Revision date
 2025-01-09

#### 9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	White
Odour	Odourless
Odour threshold	Not applicable.
pH	Not applicable.
Melting point	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Vapour Flammability	Not applicable.
Upper Explosive Limit	Not applicable.
Lower Explosive Limit	Not applicable.
Vapour pressure	Not applicable.
Relative Vapour Density	Not applicable.
Density / Relative Density	Not applicable.
Water solubility	Not applicable.
Fat Solubility	Not applicable.
Partition coefficient	Not applicable.
(n-octanol/water)	Niel as Peakle
	Not applicable.
Viscosity	
Oxidising properties	not applicable.

## 9.2. Other information

Conductivity	Not applicable.
Surface tension	Not applicable.
Specific gravity	Not applicable.
Gas group	Not applicable.

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

	Not applicable.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		
	No Significant Hazard.	
10.4. Conditions to avoid		
	Moisture.	
10.5. Incompatible materials		
	No Significant Hazard.	



Revision date 2025-01-09

### 10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.
Serious eye damage/irritation	No irritation expected.
Respiratory or skin sensitisation	No sensitizaton effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	Known Human Carcinogens (Category 1).
Reproductive toxicity	No observed effect level. No observed effect concentration.
STOT-single exposure	No known adverse health effects.
STOT-repeated exposure	Chronic effects Prolonged inhalation of respirable crystalline silica In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded: "that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis." (SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003) There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).
Aspiration hazard	No Significant Hazard.
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
11.1.4. Toxicological Information	
Cristobalite™	Oral Mouse LD50: 5000 mg/kg

### SECTION 12: Ecological information

#### 12.1. Toxicity

Cristobalite™

Fish LC50/96h: 10000.0000 mg/l

### 12.2. Persistence and degradability

No data is available on this product.

Revision 0

Revision date 2025-01-09

Partition coefficient			
	Crietobalite™ Not applicable		
12.4. Mobility in soil			
	Not determined.		
12.5. Results of PBT and vPvB assessment			
	Not determined.		
12.7 Other adverse effects			
	Not applicable.		
SECTION 13: Disposal cons	iderations		
13.1. Waste treatment methods			
	Dispose of in compliance with all. local and national regulations.		
Disposal methods			
	Contact a licensed waste disposal company.		
Disposal of packaging			
	Empty containers can be sent for disposal or recycling.		
SECTION 14: Transport information			
14.1. UN number			
	The product is not classified as dangerous for carriage.		
14.2. UN proper shipping name			
	The product is not classified as dangerous for carriage.		
14.3. Transport hazard class(es)	)		
	The product is not classified as dangerous for carriage.		
14.4. Packing group			
	The product is not classified as dangerous for carriage.		
14.5. Environmental hazards			
	The product is not classified as dangerous for carriage.		
14.6. Special precautions for user			
	The product is not classified as dangerous for carriage.		
14.7 Maritime Transport in bulk according to IMO instruments			
	The product is not classified as dangerous for carriage.		
Further information			
	The product is not classified as dangerous for carriage.		
SECTION 15: Regulatory information			

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



Re		0	

Revision date 2025-01-09

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture			
Regulations	U.S. FEDERAL REGULATIONS: SC20 family of investments. CERCLA 103 Reportable Quantity: is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.		
	SARA TITLE III: Hazard Category For Section 311/312: Chronic health quartz.		
	Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None		
	Section 302 Extremely Hazardous Substances (TPQ): None		
	EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.		
	INTERNATIONAL REGULATIONS:		
	Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).		
	Canadian WHMIS Classification: Class D2A (Chronic toxic effects), D2A (Carcinogenicity).		
15.2 Chemical safety assessment			

#### 15.2. Chemical safety assessment

	No data is available on this product.			
SECTION 16: Other information				
Other information				
Text of Hazard Statements in Section 3	Carc. 1A: H350 - May cause cancer . STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .			
Further information				
	Training			

	Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.
-	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

