

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/8

965 investment [NA]

Revision n Revision date 2016-03-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 965 investment [NA]

965 investment 031616 R519 Product code

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites;

Description Foundry material.

1.3. Details of the supplier of the safety data sheet

Company Ransom & Randolph

Address 3535 Briarfield Boulevard,

Maumee, OH 43537 USA www.ransom-randolph.com

Web Telephone +1 (419) 865-9497

Fax +1 (419) 865-9997 **Email** RR.SDS@dentsply.com

Email address of the RR.SDS@dentsply.com competent person

1.4. Emergency telephone number

USA +1 419 865 9497 **Emergency telephone number**

Company Ransom & Randolph Co.

07:30 to 16:30 (Eastern Std. / GMT minus 5)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC

1272/2008

Carc. 1A: H350; STOT RE 1: H372;

2.2. Label elements

Hazard pictograms



Signal Word

Hazard Statement

Carc. 1A: H350 - May cause cancer (lungs).

STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

inhalation

Precautionary Statement:

Prevention

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash (hands) thoroughly after handling.

Revision 0 Revision date 2016-03-16

2.2. Label elements

	P270 - Do no eat, drink or smoke when using this product.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P308+P313 - IF exposed or concerned: Get medical advice/attention.
Response	P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement:	P405 - Store locked up.
Storage	
Precautionary Statement:	P501 - Dispose of contents/container to local and national regulations
Disposal	
2.3 Other hazards	

Other hazards	Product contains crystalline silica.
	P285 - In case of inadequate ventilation wear respiratory protection.

Further information

Not applicable. PBT and vPvB assessment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Mullite (Kaolin)		1332-58-7			5 - 10%	0	
Calcium sulfate (Plaster of Paris)		26499-65-0			20 - 40%	Ó	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Mullite (Kaolin)		1332-58-7			5 - 10%		
quartz (conc. >/= 1.0%)		14808-60-7	238-878-4		20 - 40%	Carc. 1A: H350; STOT RE 1: H372;	
Calcium sulfate (Plaster of Paris)		26499-65-0			20 - 40%		
silica (cristobalite conc. >/= 1.0 %)	14464-46-1	238-455-4		20 - 40%	Carc. 1A: H350; STOT RE 1: H372;	

Further information

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash with soap and water.
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause irritation to respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	May cause irritation to mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

4.3. Indication of any infinediate medical attention and special treatment needed		
Inhalation	Seek medical attention if irritation or symptoms persist.	
Eye contact	Seek medical attention if irritation or symptoms persist.	



Revision 0 Revision date 2016-03-16

4.3 Indication of any immediate	medical attention and special treatment needed
·	·
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.
SECTION 5: Firefighting me	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising from	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear suitable protective clothing.
SECTION 6: Accidental rele	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Avoid raising dust. Wear suitable respiratory equipment when necessary.
6.2. Environmental precautions	
	No environmental requirements.
6.3. Methods and material for co	ontainment and cleaning up
	Avoid raising dust. Clean the area using a vacuum cleaner. Transfer to suitable, labelled containers for disposal.
6.4. Reference to other sections	
	See section [2, 8 & 13] for further information.
SECTION 7: Handling and s	torage
7.1. Precautions for safe handling	
	Avoid raising dust. Ensure adequate ventilation of the working area. In case of insufficient
	ventilation, wear suitable respiratory equipment.
	Do not eat, drink or smoke in areas where this product is used or stored. Wash hands after handling the product.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep containers tightly closed.
7.3. Specific end use(s)	
	Foundry material.
SECTION 8: Exposure contr	rols/personal protection
8.1. Control parameters	
	exposure limits - Silica, vitreous (fused, amorphous) 80 mg/m3 / (% Silica), TWA PEL (respirable fraction).
	exposure limits - Crystalline Silica, Cristobalite - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 10 mg/m3 / [2(% Silica + 2)] TWA PEL (respirable fraction).
	exposure limits - Crystalline Silica, quartz - 0.025 mg/m3 TWA ACGIH TLV (respirable fraction); 10 mg/m3 / (% Silica + 2) TWA PEL (respirable fraction).
8.1.1. Exposure Limit Values	




Revision 0 Revision date 2016-03-16

8.1.1. Exposure Limit Values

Calcium sulfate (Plaster of Paris)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 4	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Mullite (Kaolin)	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total 2	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls



Respiratory protection Suitable respiratory equipment.

8.2.3. Environmental exposure controls

Controls

Occupational exposure controls

Handprotection

Not normally required.

Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



Revision 0
Revision date 2016-03-16

9.1. Information on basic physical and chemical properties

Appearance Powder Colour Off white Odour Slight 6 - 8 pН Melting point No data available Freezing Point Not applicable. Initial boiling point Not applicable. **Evaporation rate** Not applicable. Flammability (solid, gas) Not applicable. Vapour pressure Not applicable. Vapour density Not applicable. Relative density 2.5 **Fat Solubility** Not applicable. Partition coefficient No data available Autoignition temperature Not applicable. Viscosity No data available **Explosive properties** Not applicable. Oxidising properties Not applicable. Solubility Slightly soluble in water

9.2. Other information

Conductivity
Surface tension
Gas group
Benzene Content
Lead content
VOC (Volatile organic compounds)

No data available
Not applicable.
Not applicable.
Vot applicable.

SECTION 10: Stability and reactivity

10).1		Rea	ctiv	∕ity
----	-----	--	-----	------	------

Not applicable.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No Significant Hazard.

10.4. Conditions to avoid

Moisture.

10.5. Incompatible materials

No Significant Hazard.

10.6. Hazardous decomposition products

Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid and produce silicone tetrafluoride. Reaction with water or acids generates heat.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.



Revision 0 Revision date 2016-03-16

11.1. Information on toxicological effects		
Serious eye damage/irritation	No irritation expected.	
Respiratory or skin sensitisation	No sensitizaton effects reported.	
Germ cell mutagenicity	No mutagenic effects reported.	
Carcinogenicity	Known Human Carcinogens (Category 1).	
Reproductive toxicity	No observed effect level. No observed effect concentration.	
STOT-single exposure	No known adverse health effects.	
STOT-repeated exposure	Chronic effects Prolonged inhalation of respirable crystalline silica In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded: "that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is sufficient information to conclude that the relative lung cancer risk is increased in persons with silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk. Since a clear threshold for silicosis development cannot be identified, any reduction of	
	exposure will reduce the risk of silicosis." (SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003) There is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required (see Section 16).	
Aspiration hazard	No Significant Hazard.	
Repeated or prolonged exposure	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.	
11.1.4. Toxicological Information		
	Not applicable.	
SECTION 12: Ecological info	ormation	
12.1. Toxicity		
	No data available	
12.2. Persistence and degradab	ility	
	No data is available on this product.	
12.3. Bioaccumulative potential	· · · · · · · · · · · · · · · · · · ·	
<u> </u>		
	Does not bioaccumulate.	
Partition coefficient		
	965 investment [NA] No data available	
12.4. Mobility in soil		
	Not determined.	
12.5. Results of PBT and vPvB assessment		
12.0. Results Of For allu YPVD		
	Not determined.	



0 Revision Revision date 2016-03-16

12.6. Other adverse effects			
	Not applicable.		
SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
	Dispose of in compliance with all. local and national regulations.		
Disposal methods			
	Contact a licensed waste disposal company.		
Disposal of packaging			
	Empty containers can be sent for disposal or recycling.		
SECTION 14: Transport information			
14.1. UN number			
	The product is not classified as dangerous for carriage.		
14.2. UN proper shipping name			
	The product is not classified as dangerous for carriage.		
14.3. Transport hazard class(es)			
	The product is not classified as dangerous for carriage.		
14.4. Packing group			
	The product is not classified as dangerous for carriage.		
14.5. Environmental hazards			
	The product is not classified as dangerous for carriage.		
14.6. Special precautions for user			
	The product is not classified as dangerous for carriage.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			
	The product is not classified as dangerous for carriage.		
Further information			
	The product is not classified as dangerous for carriage.		
SECTION 15: Regulatory information			

OLOTTON 13. Regulatory IIII	omaton		
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture			
Regulations	U.S. FEDERAL REGULATIONS:		
	CERCLA 103 Reportable Quantity: 965 investment is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.		
	SARA TITLE III: Hazard Category For Section 311/312: Chronic health		
	Section 313 Toxic Chemicals: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None		
	Section 302 Extremely Hazardous Substances (TPQ): None		
	EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.		
	U.S. STATE REGULATIONS		



Revision 0
Revision date 2016-03-16

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

California Proposition 65: This product contains the following substances known to the State of California to cause cancer: Crystalline Silica as Cristobalite and Quartz (< 70 %);

INTERNATIONAL REGULATIONS:

Canadian Environmental Protection Act: All of the components in this product are listed on the Domestic Substances List (DSL).

Canadian WHMIS Classification: Class D2A (Chronic toxic effects), D2A (Carcinogenicity).

15.2. Chemical safety assessment

No data is available on this product.

SECTION 16: Other information

Other information

Text of Hazard Statements	in
Section 3	

Carc. 1A: H350 - May cause cancer.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

Further information

Training

Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations.

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

