

## SAFETY DATA SHEET according to Regulation (EU) 2015/830

Page 1/7

## SC-D, SC-D EW investment [EU] (Draft)

Revision 0 (Draft) Revision date

SECTION 1. Identification of	the substance/mixture and of the company/undertaking
I.1. Product identifier	
Product name	SC-D, SC-D EW investment [EU]
I.2. Relevant identified uses of t	the substance or mixture and uses advised against
Description	Foundry material.
1.3. Details of the supplier of the	e safety data sheet
Company	Ransom & Randolph
Address	3535 Briarfield Boulevard, PO Box 1570
	Maumee, Ohio 43537 USA
Web	www.ransom-randolph.com
Telephone	+1 (419) 865-9497
Fax	+1 (419) 865-9997
Email	RR.SDS@dentsply.com
Email address of the	RR.SDS@dentsply.com
competent person	
.4. Emergency telephone num	Der
Emergency telephone number	USA +1 419 865 9497
Company	Ransom & Randolph Co.
	08:00-17:00 (US Eastern Std. / GMT minus 5)
SECTION 2: Hazards identif	ication
2.1. Classification of the substar	nce or mixture
2.1.2. Classification - EC 1272/2008	Repr. 1B: H360FD; STOT RE 1: H372;
2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	Repr. 1B: H360FD - May damage fertility. May damage the unborn child.
	STOT RE 1: H372 - Causes damage to organs (lungs) through prolonged or repeated exposure inhalation.
Precautionary Statement:	P201 - Obtain special instructions before use.
Prevention	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
	P264 - Wash thoroughly after handling.
	P270 - Do no eat, drink or smoke when using this product. P280 - Wear protective gloves/protective clothing/eye protection/face protection.



Revision 0 (Draft)

**Revision date** 

2.2. Label elements	
Precautionary Statement: Response	P308+P313 - IF exposed or concerned: Get medical advice/attention. P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to local and national regulations
2.3. Other hazards	
Other hazards	Product contains respirable crystalline silica (RCS).
	Not applicable. PBT and vPvB assessment.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
silica - crisbotabile EU.		14464-46-1	238-455-4		40 - 50%	STOT RE 1: H372;
quartz > 10 % EU (Quartz)		14808-60-7	238-878-4		30 - 40%	STOT RE 1: H372;
calcium sulfate. (Plaster of Paris)		26499-65-0			20 - 30%	
boric acid	005-007-00-2	10043-35-3	233-139-2		0.5 - 1%	Repr. 1B: H360FD;

#### **Further information**

Full text for all Risk Phrases mentioned in this section are displayed in Section 16.

#### SECTION 4: First aid measures 4.1. Description of first aid measures Inhalation Move the exposed person to fresh air. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Eye contact Skin contact Wash with soap and water. Ingestion Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING. 4.2. Most important symptoms and effects, both acute and delayed May cause irritation to respiratory system. Inhalation Eye contact May cause irritation to eyes. Skin contact May cause irritation to skin. Ingestion May cause irritation to mucous membranes. 4.3. Indication of any immediate medical attention and special treatment needed Inhalation Seek medical attention if irritation or symptoms persist. Eye contact Seek medical attention if irritation or symptoms persist. Skin contact Seek medical attention if irritation or symptoms persist. Ingestion Seek medical attention if irritation or symptoms persist.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Use extinguishing media appropriate to the surrounding fire conditions.

### 5.2. Special hazards arising from the substance or mixture


Burning produces irritating, toxic and obnoxious fumes.



Revision 0 (Draft)

**Revision date** 

5.3. Advice for firefighters		
	Self-contained breathing apparatus. W	ear suitable protective clothing.
SECTION 6: Accidental relea	ase measures	
6.1. Personal precautions, prote	ctive equipment and emergency procedu	ires
	Avoid formation of dust.	
6.2. Environmental precautions		
	Use appropriate container to avoid env	ironmental contamination.
6.3. Methods and material for co	ontainment and cleaning up	
	Avoid raising dust. Clean the area usin	g a vacuum cleaner. Transfer to suitable, labelled container.
6.4. Reference to other sections		
	See section [2, 8 & 13] for further inform	nation.
SECTION 7: Handling and s	torage	
7.1. Precautions for safe handlin	Ig	
	exposure limit.	ate ventilation of the working area. <. OEL: Occupational ere this product is used or stored. Wash hands after
7.2. Conditions for safe storage,	including any incompatibilities	
	Keep containers tightly closed.	
7.3. Specific end use(s)		
	Foundry material.	
SECTION 8: Exposure contr	ols/personal protection	
8.1. Control parameters		
	OEL: Occupational exposure limit. qua mg/m3 (respirable fraction).	rtz - 0.1 mg/m3 (respirable fraction); cristobalite - 0.1
8.1.1. Exposure Limit Values		
calcium sulfate. (Plaster of	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: -
Paris)	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total 10	WEL 15 min limit mg/m3 total
	inhalable dust: WEL 8-hr limit mg/m3 total 4	inhalable dust: WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
quartz > 10 % EU (Quartz)	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: .1
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:



#### 8.2. Exposure controls





Revision 0 (Draft)

**Revision date** 

8.2. Exposure controls	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area. <. OEL: Occupational exposure limit.
8.2.2. Individual protection measures	Wear protective clothing. EN13982, ANSI 103 or =.
Eye / face protection	Avoid contact with eyes. Wear:. Approved safety goggles. safety glasses with side-shields. EN166, ANSI Z87.1 or =.
Skin protection - Handprotection	Avoid contact with skin. Wear suitable gloves. EN374, ASTM F1001 or =.
Respiratory protection	Exposure above the recommended occupational exposure limit (OEL) may cause adverse health effects. Wear:. Suitable half mask respirator with filter P3 (EN 143). EN140, EN143, ASTM F2704-10 or =.
8.2.3. Environmental exposure controls	Use appropriate container to avoid environmental contamination.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Powder
Colour	White
Odour threshold	Not applicable.
pH	6 - 8
Melting point	Not applicable.
Freezing Point	Not applicable.
Initial boiling point	Not applicable.
Flash point	No data available
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Vapour pressure	No data available
Vapour density	Not applicable.
Relative density	2.2 - 2.7
Fat Solubility	Not applicable.
Partition coefficient	Not applicable.
Autoignition temperature	Not applicable.
Viscosity	No data available
Explosive properties	No data available
Oxidising properties	Not applicable.
Solubility	Slightly soluble in water

### 9.2. Other information

Conductivity	Not applicable.
Surface tension	Not applicable.
Gas group	Not applicable.

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

	Not applicable.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		

### No Significant Hazard.

## 10.4. Conditions to avoid



Revision 0 (Draft)

**Revision date** 

	Revision date			
10.4. Conditions to avoid				
	No Significant Hazard.			
10.5. Incompatible materials				
	No Significant Hazard.			
10.6. Hazardous decomposition products				
	Hazardous Decomposition Products (silica): Crystalline silica will dissolve in hydrofluoric acid			
	and produce silicone tetrafluoride. Reaction with water or acids generates heat.			
SECTION 11: Toxicological	information			
11.1. Information on toxicologica	al effects			
Acute toxicity	Not applicable. Based on available data, the classification criteria are not met.			
Skin corrosion/irritation	Not applicable. Based on available data, the classification criteria are not met.			
Serious eye damage/irritation	Not applicable. Based on available data, the classification criteria are not met.			
Respiratory or skin sensitisation	Not applicable. Based on available data, the classification criteria are not met.			
Germ cell mutagenicity	Not applicable. Based on available data, the classification criteria are not met.			
Carcinogenicity	Based on available data, the classification criteria are not met.			
Reproductive toxicity	May impair fertility.			
	May cause harm to the unborn child.			
STOT-single exposure	Not applicable. Based on available data, the classification criteria are not met.			
STOT-repeated exposure	Chronic effects			
	Prolonged inhalation of respirable crystalline silica			
	In 1997, the International Agency for Research on Cancer (IARC) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that			
	not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC			
	Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates			
	dust and organic fibers, 1997, Vol. 68, IARC, Lyon, France). In June 2003, the European			
	Commission's Scientific Committee for Occupational Exposure Limits (SCOEL) concluded:			
	"that the main effect in humans of the inhalation of respirable crystalline silica is silicosis. There is			
	sufficient information to conclude that the relative lung cancer risk is increased in persons with			
	silicosis (and apparently, not in employees without silicosis exposed to silica dust in quarries and			
	in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer			
	risk. Since a clear threshold for silicosis development cannot be identified, any reduction of exposure will reduce the risk of silicosis."			
	(SCOEL SUM Doc 94-final on respirable crystalline silica, June 2003)			
	There is a body of evidence supporting the fact that increased cancer risk would be limited to			
	people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk			
	management measures where required (see Section 16).			
Aspiration hazard	Not applicable. Based on available data, the classification criteria are not met.			
Repeated or prolonged exposure	Inhalation of dust may cause shortness of breath.			
11.1.4. Toxicological Information	 1			
SC-D, SC-D EW investment	Oral Mouse LD50: 5000 mg/kg			
[EU]				

## SECTION 12: Ecological information

12.1. Toxicity



Revision 0 (Draft)

**Revision date** 

12.1. Toxicity	
SC-D, SC-D EW investment [EU]	Fish LC50/96h: 10000.0000 mg/l
12.2. Persistence and degradat	
	Not applicable.
12.3. Bioaccumulative potential	·
	Does not bioaccumulate.
Partition coefficient	
	SC-D, SC-D EW investment Not applicable. [EU]
12.4. Mobility in soil	
	Not determined.
12.5. Results of PBT and vPvB	assessment
	Not determined.
12.6. Other adverse effects	
	Not applicable.
SECTION 13: Disposal cons	siderations
13.1. Waste treatment methods	
	Dispose of in compliance with all. local and national regulations.
Disposal methods	
	Contact a licensed waste disposal company.
Disposal of packaging	
	Do NOT reuse empty containers. Empty containers can be sent for disposal or recycling.
Further information	
	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
SECTION 14: Transport info	prmation
14.1. UN number	
	The product is not classified as dangerous for carriage.
14.2. UN proper shipping name	
	The product is not classified as dangerous for carriage.
14.3. Transport hazard class(es	
	The product is not classified as dangerous for carriage.
14.4. Packing group	
	The product is not classified as dangerous for carriage.
14.5. Environmental hazards	
	The product is not classified as dangerous for carriage.
14.6. Special precautions for us	
	The product is not classified as dangerous for carriage.
14.7. Transport in bulk accordin	g to Annex II of MARPOL 73/78 and the IBC Code



Revision 0 (Draft)

**Revision date** 

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### The product is not classified as dangerous for carriage.

Further information

The product is not classified as dangerous for carriage.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No data is available on this product.

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

## 15.2. Chemical safety assessment

## SECTION 16: Other information

#### Other information

	Training Workers must be informed of the presence of crystalline silica and trained in the proper use and handling of this product as required under applicable regulations. Social Dialogue on Respirable Crystalline Silica A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union
	October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from http://www.nepsi.eu and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers,. STOT RE1: H372 - DANGER - Causes damage to lungs through prolonged or repeated exposure by inhalation.
Text of Hazard Statements in Section 3	STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure . Repr. 1B: H360FD - May damage fertility. May damage the unborn child.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

